

## SYMBOL SCHEDULE

[illegible]

**PANEL 'A'**  
BASEMENT

[illegible]

## FIXTURE SCHEDULE

PRIMER TYPE	LMF	HEADING
(A) LITMUNA M13-32-1MOL-115-GENOTIPS	(B) 32M 15 (4M)	SURFACE CELLING
(B) LITMUNA M95-2-33-1MOL-1-GENOTIPS	(D) 33M 14 (M)	SURFACE CELLING OR SURFACE WALL, 1° & 6° AF
(C) LITMUNA M16M-12-121M-1MOL-1-GENOTIPS	42M 1RT	RECEIVED CELLING
(D) LITMUNA M66M-4-2121M-1MOL-1-1-GENOTIPS	42M 1RT	SURFACE CELLING
(E) LITMUNA M602-32-321M-1MOL-1-GENOTIPS	32M 1RT	SURFACE WALL, 0° AF
(F) LITMUNA M16M-100M-1B-1M	100M 1RT	SURFACE WALL, 12° AF
(G) GENOTIP PORCELANITE GENOTIPS M16M (M)	100M AF	CELLING WALL, HONDED AS INDICATED

## EMERGENCY LIGHTING UNIT SCHEDULE

UNIT NUMBER	CATALOGUE NUMBER
BM-1	READY-LITE #BX26-28Q12-MEX1N
BM-2	READY-LITE #1DX6-21-28Q12
BM-3	READY-LITE #1DX12-44-28Q12
BM-4	READY-LITE #1DX12-40Q-2819
BM-5	READY-LITE #1DX12-17-28Q12
BM-6	READY-LITE #1DX6-21-28Q12

Traditions  
Designs West

[illegible]

PROJECT :  
ST. JOSEPH'S CHURCH  
FOOD BANK

32550 - 7th AVENUE - MISSION BC

## MECHANICAL EQUIPMENT SCHEDULE


UNIT #	DESCRIPTION	LOCATION	LOAD	VOLTS	PHASE	WIRE SIZE	SWITCH	DISCONNECT	PLANT DEVICE	EXP. RISK	REMARKS
EF-1	EXHAUST FAN	BASEMENT MECH ROOM	24 M	120	1	2#2 BSC	1 P 1 D	50 AMP	1 P 5 R	E	INTERLOCK WITH LIGHT SWITCH
EF-2	EXHAUST FAN	MECH FLOOR MECH ROOM	44 M	120	1	2#2 BSC	1 P 1 D	50 AMP	1 P 5 R	E	INTERLOCK WITH LIGHT SWITCH
EF-3	EXHAUST FAN	MAIN FLOOR MECH ROOM	44 M	120	1	2#2 BSC	1 P 1 D	50 AMP	1 P 5 R	E	INTERLOCK WITH LIGHT SWITCH
HF-1	CONDENSING UNIT	OUTSIDE OF BUILDING	211 KVA	208	3	3#0 BSC	3 P 3 D	300 AMP	3 P 3 R	N	INTERLOCK WITH PROGRAMMABLE 15-STAT
HF-2	FAN COIL UNIT WITH BURN HEATER	MECHANICAL CLOSET	471 KVA	208	3	3#6 BSC	3 P 3 D	300 AMP	3 P 3 R	N	PROGRAMMABLE 15-STAT

**E<sup>i</sup>** DENOTES RESPONSIBILITY OF ELECTRICAL CONTRACTOR  
**M** DENOTES RESPONSIBILITY OF MECHANICAL CONTRACTOR

DEVICES  
= FLOA  
= THER  
= POES

HT-1	HOT WATER PANK	MECHANICAL CLOSET	15 KN	120	1	Y	2#2 PERO	N
HT-1	CONNECTOR	SHUTT BUREAU/ENTR	5 MP	200	3	Y	3#2 PERO	N
								STARTER TO BE CHARGE OF PERSONS CONTROL OPERATION

## EXTERIOR LIGHTING CONTROL



NOTES:

1. PHOTOCELL TO BE EQUAL TO TORK CAT. #2101.
2. RELAYS TO BE RATED AT 30A 600V C/W 120V COIL.
3. LOCATE LIGHTING CONTROLS IN UTILITY ROOM BY PANEL 'A'.

## GROUNDING & BONDING NOTES

1. ELECTRICAL CONTRACTOR IS TO INSTALL GROUNDING AT THE NEW FOOD BANK BUILDING AS PER THE CURRENT EDITION OF THE CANADIAN ELECTRICAL CODE REQUIREMENTS.

**CONSULTANT :**  
Electrical Consultant:



©  
COPYRIGHT RESERVED.  
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF  
MURPHY DESIGN SERVICES INC.  
AND UNAUTHORIZED REPRODUCTION IS PROHIBITED.

DRAWING TITLE :

SCHEDULES &  
SCHEMATICS

DATE : JAN. 2011

SCALE : AS NOTED

JOB NO : TW1012

DR

SHEET